

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Currently Amended) A loudspeaker apparatus comprising:

an elongate printed circuit board having a plurality of terminals and having a length greater than a width; and

a plurality of loudspeakers mounted on the printed circuit board along its length in a substantially straight configuration, each terminal of the plurality of terminals for inputting a signal of the loudspeakers being electrically coupled with a conductive pattern part of the printed circuit board,

wherein signal inputting parts for inputting a signal from an outside are formed by leading the conductive pattern part to at least both ends of the printed circuit board in the longitudinal direction,

wherein each of said loudspeakers covers most of a distance extending from edge to edge of said printed circuit board, and

wherein the loudspeakers are electrically coupled with one another.

2. (Currently Amended) The loudspeaker apparatus of claim 1,

wherein at least one of the ~~signal inputting parts~~plurality of terminals is a terminal directly connected with a connector which is coupled with another printed circuit board or a printed board.

3. (Previously Presented) The loudspeaker apparatus of claim 1, wherein the impedance of the loudspeakers is equalized or approximated to an impedance of one loudspeaker

4. (Original) The loudspeaker apparatus of claim 3,

wherein the loudspeakers are electrically coupled in series.

5. (Previously Presented) The loudspeaker apparatus of claim 1,

wherein a high cut filter, which restrains an input at high frequencies of at least one terminal-section-side loudspeaker of the loudspeakers, is coupled with the conductive pattern part.

6. (Previously Presented) The loudspeaker apparatus of claim 2,

wherein the loudspeakers are electrically coupled with one another, and its impedance is equalized or approximated to an impedance of one loudspeaker.

7. (Previously Presented) The loudspeaker apparatus of claim 2,

wherein a high cut filter, which restrains an input at high frequencies of at least one terminal-section-side loudspeaker of the loudspeakers, is coupled with the conductive pattern part.

8. (Previously Presented) The loudspeaker apparatus of claim 6,

wherein the loudspeakers are electrically coupled in series.